

## html.html.twig

<code>\$css</code>	A list of CSS files for the current page.
<code>\$head</code>	Markup for the HEAD element (meta tags, keyword tags, etc)
<code>\$head_title</code>	Modified version of page title, in the TITLE tag.
<code>\$head_title_array</code>	List of text elements of <code>\$head_title</code> . May contain: title: The title of the page. name: The name of the site. slogan: The slogan of the site.
<code>\$page</code>	The rendered page markup.
<code>\$page_top</code> , <code>\$page_bottom</code>	Initial and closing rendered markup. This should be printed before and after 'page' respectively.
<code>\$scripts</code> , <code>\$styles</code>	Script and style tags necessary to load JS and CSS files and settings in the head.

## page.html.twig

<code>\$action_links</code>	Actions local to the page eg. "Add menu" on the menu administration interface.
<code>\$base_path</code>	The base URL path of the Drupal installation, usually "/" unless Drupal in sub-directory.
<code>\$breadcrumb</code>	The breadcrumb trail for the current page.
<code>\$front_page</code>	The URL of the front page. Use instead of <code>base_path</code> when linking to front page. includes the language domain/prefix.
<code>\$feed_icons</code>	All feed icons for the current page.
<code>\$is_admin</code>	Flag: if user has access administration pages.
<code>\$is_front</code>	Flag: if current page is front page.
<code>\$logged_in</code>	Flag: if user registered & signed in.
<code>\$logo</code>	The url of the logo image (in theme settings)
<code>\$main_menu</code>	The main menu links for the site
<code>\$secondary_menu</code>	The secondary menu links for the site
<code>\$messages</code>	Status/error messages. Display prominently
<code>\$page.header</code>	Items for the header region.
<code>\$page.highlighted</code>	Items for the highlighted content region.
<code>\$page.help</code>	Dynamic help text, mostly for admin pages.
<code>\$page.content</code>	The main content of the current page.
<code>\$page.sidebar_first</code>	Items for the first sidebar.
<code>\$page.sidebar_second</code>	Items for the second sidebar.
<code>\$page.footer</code>	Items for the footer region.
<code>\$node</code>	Fully loaded node, if an automatically-loaded node is associated with the page
<code>\$site_name</code> , <code>\$site_slogan</code>	The name, slogan of the site. Empty when displaying is disabled in the theme settings.
<code>\$tabs</code>	Tabs linking to any sub-pages beneath the current page (e.g., the view and edit tabs when displaying a node).
<code>\$title</code>	The page title, for use in the actual content.
<code>\$title_prefix</code> , <code>\$title_suffix</code>	Additional output populated by modules, intended to be displayed in front of or after the main title tag that appears in the template.

## comment.html.twig

<code>\$comment (object)</code>	Full comment object
<code>\$entity</code>	Entity the comments are attached to.
<code>\$author</code>	Comment author. A link or plain text.
<code>\$attributes.class</code>	List of classes; can be used to style through CSS
<code>\$content</code>	Content-related items for comment display. <code>{{ content }}</code>
<code>\$created</code>	Formatted date & time for when comment created.
<code>\$changed</code>	Formatted date & time for when comment last changed.
<code>\$permalink</code>	Comment permalink.
<code>\$submitted</code>	Submission information created from author and created during <code>template_preprocess_comment()</code> .
<code>\$user_picture</code>	The comment author's profile picture.
<code>\$signature</code>	The comment author's signature.
<code>\$status</code>	Unpublished, published, or preview.
<code>\$title</code>	Comment title, linked to the comment.
<code>\$title_prefix</code> , <code>\$title_suffix</code>	Additional output populated by modules, intended to be displayed in front or after the main title tag that appears in the template.
<code>\$content_attributes</code>	List of classes for styling of the comment content.

## node.html.twig

<code>\$node (object)</code>	The node object.
<code>-&gt;id</code>	The node ID
<code>-&gt;bundle</code>	The type of the node, for example, "page" or "article".
<code>-&gt;authored</code>	The user ID of the node author.
<code>-&gt;createdtime</code>	Formatted creation date. Preprocess functions can reformat it by calling <code>format_date()</code>
<code>-&gt;promoted</code>	Whether the node is promoted to front page.
<code>-&gt;sticky</code>	Whether the node is 'sticky'
<code>-&gt;published</code>	Whether the node is published.
<code>\$label</code>	The title of the node.
<code>\$content</code>	All node items. Use <code>{{ content }}</code> to print them all Use <code>{{ content.field_example }}</code> for subset. Use <code>{% hide(content.field_example) %}</code> to hide
<code>\$user_picture</code>	The node author's picture
<code>\$date</code>	Formatted creation date. Preprocess functions can reformat it by calling <code>format_date()</code>
<code>\$name</code>	Themed username of node author output
<code>\$node_url</code>	Direct URL of the current node.
<code>\$display_submitted</code>	Whether submission information be displayed.
<code>\$submitted</code>	Submission information created from name and date during <code>template_preprocess_node()</code> .
<code>\$attributes</code>	HTML attributes for the containing element.
<code>\$title_prefix</code> , <code>\$title_suffix</code>	Additional output populated by modules, intended to be displayed in front or after the main title tag that appears in the template.
<code>\$view_mode</code>	View mode; for example, "teaser" or "full". Flags: <code>\$teaser</code> , <code>\$page</code>
<code>\$readmore</code>	Flag: more state. true if teaser content of the node cannot hold the main body content.
<code>\$is_front</code>	Flag: front. true when on the front page.
<code>\$logged_in</code>	Flag: authenticated user status. true when the current user is a logged-in member.
<code>\$is_admin</code>	Flag: admin user status. Will be true when the current user is an administrator.

## block.html.twig

<code>\$block (object)</code>	The block object
<code>-&gt;label_hidden</code>	The hidden block title value if configured to hide the title ('label' is empty in this case).
<code>-&gt;module</code>	The module that generated the block.
<code>-&gt;delta</code>	An ID for the block, unique within each module.
<code>-&gt;region</code>	The block region embedding the current block.
<code>\$plugin_id</code>	The ID of the block implementation.
<code>\$label</code>	The configured label of the block if visible.
<code>\$attributes</code>	HTML attributes for the containing element..
<code>\$configuration</code>	A list of the block's configuration values.
<code>\$content</code>	The content of this block.
<code>\$title_attributes</code>	HTML attributes for the title element.
<code>\$content_attributes</code>	HTML attributes for the content element.
<code>\$title_prefix</code> , <code>\$title_suffix</code>	Additional output populated by modules, intended to be displayed in front or after the main title tag that appears in the template.

## context about parent comment:

<code>\$comment_parent</code>	Full parent comment entity (if any).
<code>\$parent_author</code>	<code>\$author</code> of parent comment.
<code>\$parent_created</code>	<code>\$created</code> of parent comment.
<code>\$parent_changed</code>	<code>\$changed</code> of parent comment.
<code>\$parent_title</code>	<code>\$title</code> of parent comment.
<code>\$parent_permalink</code>	<code>\$permalink</code> of parent comment.
<code>\$parent</code>	Text string of parent comment submission info